

# Assembly fittings

for pressure gauges and pressure transmitters

## In-line filter

E 09.06.02

Ed.12.01


### In-line Filter

Pressure gauge in-line filters are installed to filter out solid substances of gaseous and liquid media. They avoid: Plugging of small gauge pressure entries and capillary throttles. Accumulation of particles in dirt-sensitive gauge interiors. Further they have an effect of a throttle and damp shock pressure.

Temperature range -25+200°C

Max pressure rate PN 100 bar with gasket of PTFE

Max pressure rate PN 1600 bar with gasket of stainless steel 1.4571



Type	Male G <sub>1</sub>	Female G <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	SW	Code
9200	G1/2"	G1/2"	7	6	3,5	46	19	20	22	3	27	92000000
9203	G1/4"	G1/4"	5,5	5	3	32	13	13	15	2	17	92030000

### Gasket for female connection G<sub>2</sub>

Type	Connection	Material	Max pressure	Code
9208	G1/4"	PTFE 0,5 mm	100 bar	92080000
9216	G1/4"	stainless steel 1.4571	1600 bar	92160000
9117	G1/2"	PTFE 0,5 mm	100 bar	91170000
9209	G1/2"	stainless steel 1.4571	1600 bar	92090000

### Spare parts

1/2" filter of stainless steel - Code **9206 0000**

1/4" filter of stainless steel - Code **9207 0000**

